

DESCRIPTION

Decorative LED luminary with direct lighting for suspending with a high-performance opal diffuser. Body made of high quality extrusion aluminum, oven-lacquered and textured finishes. Accessories included.

EFFECTIVE LIGHTING INFORMATION

| | |
|-----------------|-----------|
| Lighting flux: | 7420 lm |
| LED efficiency: | 83,4 lm/w |
| Consumption: | 89 W |
| Openning angle: | 107,00 |

LED FEATURES

| | |
|----------------------------|--------------------|
| Colour temperature: | 4000K |
| LED efficiency: | >160 lm/w @TA=25°C |
| MacAdam Ellipse: | 3 |
| Lifetime: | 50.000H @TA=25° |
| Lighting flux maintenance: | L80 |
| LED deterioration: | B10 |
| CRI: | 80 |

FEATURES OF THE LUMINARY

| | |
|-----------------------|------------|
| Diffuser: | OPAL |
| Type of luminary: | IND |
| Colour: | NG |
| Electronic equipment: | TRIDONIC |
| Installation: | SUSPENDIDA |
| Waterlightness: | IP40 |
| Mechanical resistor: | IK04 |
| Weight: | 12,00 |
| Guarantee | 5 years |

ELECTRICAL INFORMATION

| | |
|--------------------|-------------------|
| Voltage/Frequency: | 220-240 v / 50 hz |
| Regulation: | NO |
| Isolation Type: | Class 1 |

